

Declaration of conformity in accordance with EU Directive 2014/68/EU (Pressure Equipment Directive)

RITAG
Ritterhuder Armaturen GmbH & Co. Armaturenwerk KG
Sachsenring 30
D-27711 Osterholz-Scharmbeck

RITAG tank bottom valves of types

BA, BAS, BV and BVS

Nominal diameter: DN32 – DN600, 1 ¼" – 24"

Nominal pressure: PN6 – PN100, Class 150 – Class 600

Category I, II and III, fluid group 2 (*valves for fluid group 1 see below!*)

Applied conformity assessment procedures:
H (Full Quality Assurance)

Surveillance under the responsibility of

Lloyds Register Deutschland GmbH
Überseeallee 10
20457 Hamburg

CE 0525

Applied harmonised norms and standards:

EN 12516, EN 1503, EN 10028, EN 10213, EN 10216, EN 10272, EN 10273, EN 12266,
EN 13445, ISO 5208, AD 2000-Regelwerk, EN ISO 3834 and others.

Additionally applied norms and standards:

ASME B16.34, API 598

Materials:

Ferritic, austenitic, duplex materials in cast and forged versions and non-ferrous metals

RITAG tank bottom valves for fluid group 1:

The following RITAG bottom valves may be used for fluid group 1:

- Valves with sealing systems that correspond to the requirements of TA-Luft or comparable regulations. This is to be agreed/ordered separately.

RITAG tank bottom valves nominal diameter DN25 and smaller:

The valves stated above correspond to the requirements of DGRL2014/68/EU in the same way, but are not indicated with **CE** in accordance with article 4 paragraph 3.

Osterholz-Scharmbeck, 28.07.2020


A. Nagel
Technical Director